



Profil Section	Breite/Höhe Width/Height (≈ kg/m)	Gewicht Weight (≈ kg/m)	Standard			Polyester	
			grün green	braun brown, abriebfest, ölbeständig abrasion and oil resistant	weiß white, abriebfest abrasion resistant	braun brown, abriebfest, ölbeständig abrasion and oil resistant	weiß white, abriebfest abrasion resistant
13 x 20	20 x 16,5	0,32	■	■	■•	■•	■•
17 x 30	30 x 20	0,46	■	■	■•	■•	■•
22 x 40	40 x 24	0,74	■	■	■•	■•	■•
32 x 60	60 x 33	1,30	■•	■•	■•	■•	■•

Profil Section	Breite/Höhe Width/Height (≈ kg/m)	Plattenverbinder <i>Plate connectors</i>		Gelenkverbinder <i>Link connectors</i>		Mindest- Scheiben- durchmesser <i>Minimum pulley diameter</i> (mm)
		Gewicht <i>Weight</i> (≈ kg/100 Stück <i>pieces</i> )		Gewicht <i>Weight</i> (≈ kg/100 Stück <i>pieces</i> )		
13 x 20	20 x 16,5	0,6	■○	2,6	—	140
17 x 30	30 x 20	0,9	■	3,7	—	160
22 x 40	40 x 24	1,8	■○	5,4	—	250
32 x 60	60 x 33	5,6	■○	5,7	—	450

Optimat Keilriemen OE, DK und FK werden in Rollenlängen von ca. 50 m hergestellt.  
*Optimat belting OE, DK and FK are supplied in lengths of approx. 50 metres.*

- Keine Lagerware, Mindestmenge *Non stock items, minimum order quantity*: 1 Rolle *roll*
- Auslaufartikel *These items will be discontinued when present stock is depleted.*